#	PART	QTY.		
1	Ramsey 251128/295137 Channel	1	Tighten to 57 ft-lb (77 Nm)	
2	Ramsey 251152 Hawse Fairlead	1		
3	Ramsey REP-6000 Winch Assembly	1	$\overline{\mathfrak{A}}$	
4	Driver Side Tow Eye	1		
5	Passenger Side Tow Eye	1		
6	5/16" Front Channel Spacer	2		
7	1/2" Rear Channel Spacer	2		
8	1/2" ID (7/16" USS) Grade 5 Washer	4		
9	1/2"-13 x 2" Grade 5 Hex Bolt	4		
10	3/8" ID (5/16" USS) Grade 5 Washer	4	$ \left  \begin{array}{c} (5) \\ \end{array} \right  $	
11	3/8" Grade 5 Split Lock Washer	6		
_	3/8"-16 Grade 5 Hex Nut	6		
	3/8"-16 x 1-1/8" Grade 5 Hex Bolt	2		
14	3/8"-16 x 1-1/4" Grade 5 Hex Bolt	4		
	Notes:  1 Ramsey 251128 production as of 2021			
1.	Ramsey 251128 production as of 2	021		
	does not match the 1992 design shown. Substitute HFT 90476 or 624	46		
	for a more visually accurate style.	10		
2.	For greater strength, substitute #8			
	#9 for Grade 8 and tighten to 80 f	t-lb.		
3.	For greater strength, substitute on winch feet only #10, #11, #12, and	7		
	#14 for Grade 8 and tighten to 33			
4.	For superior corrosion resistance,			
	substitute on hawse fairlead only #	ŧ11,		
	#12 and #13 for stainless steel.			
		/		
	(12)			
	(2)		$/ \qquad (11) \qquad                               $	
		T: ~:	bton to 22 ft lb (21 Nm)	
K'	YTOR.COM	пg	hten to 23 ft-lb (31 Nm) / (14)	