



1992 Jeep Wrangler Metric Painting Guide

For more information, please visit

JPMOTORPOOL.COM

Numbers are 25.4 Tall. Placement should be 3.81 below hood seam, and 5.7 above edge of flair. Numbers centered on Stripe. (Exact location depends on numbers chosen. Ex: 18 is narrower than 29)

Red Stripe is painted with the doors ON. Both the upper and lower halves of the TOP barrel hinge are painted red.

Edge of EXTERIOR Body, NOT Interior door jamb.

Back stripe does NOT extend under soft top retaining channel.

Measure to Tub Seam, NOT rear tub edge

Door handles and Locks remain stock/unpainted.

73°
(Parallel to rear edge)

Movie has line going over flare at 90° to flair itself. DOES NOT follow same angle as upper edge

24.8

18.4

Chrome lug nuts are painted Red (excluding spare tire)

End line at seam of Flare

3cm Measured from seam of flare to back stripe edge where flare meets tub/body

No Sahara Logo
Jeep



Note: Flair and Stripe Edge are NOT parallel

Painting with flair on: Line ends at the back edge of the front flair

Painting with flair off: Line ends at approx 7cm from the tub's wheel well.

73°

Unlike the Front flare, the Rear Flair is painted with the angle continuing OVER the flair.

End of stripe edge is slightly in front of center of wheel

Wheel Center Cap

All dimensions are in Centimeters.

Recommended Painting Steps:

- 1: Paint entire Jeep "Sand Beige"
- 2: Tape off Stripes, and apply stencil decals.
 - A: Apply both the hood AND side digit decal stencils.
- 3: Apply chosen Red Paint
- 4: Carefully remove tape/stencils and enjoy!

Detailed Build Guide and More Information at
jpmotorpool.com/reference/jeep/jeep_guide.html

Jeep Illustration by Mark Jurgiel.
 New 2017 PDF information overlay by Adam Mark

